



smartVAC

The newest Vacuum Sealers for VACUUM packaging your products

**Outstanding Value. Made in America.
Unmatched Product Quality.
Loaded with Standard Features.**



Performance

Built tough to handle industrial production environments and have user-friendly controls that operators can learn in minutes. Open ended seal bars, retractable vacuum nozzle enhance production speed. Standard features include low pressure jaw close and emergency stop switch. The smartVACuum sealer is designed for use on a tabletop or a stand and is available with a product support tray.

Value and Delivery

The 675 offers you the best possible pricing and delivery. We have designed three models in this 675 smartVAC series. Designed so you can easily select the machine with the features you need eliminating costly custom add-on's and lengthy delivery time.

Customer Service

Our sales and technical support teams are ready to assist you when you call. "Talk to a real person", not voicemail, about your application.

Built-to-Last Reliability

Accu-Seal machines are designed and built with the highest quality components and manufacturing techniques to ensure unmatched product quality and many years of reliable, trouble free service. Accu-Seal machines are all designed for easy installation, operation and maintenance.

Select the model with the built in features that fit your packaging process:

smartVAC - Model 1: Vacuum Sealer

*Vacuum-Seal
Seal only*

smartVAC - Model 2: Gas Vacuum Sealer

*Vacuum-Seal
Gas - Vacuum - Seal
Seal only*

smartVAC - Model 3: Multi-Stage Vacuum

Sealer Multiple Seal Modes (6), with multi-cycle (1-99), independent Vac1 & Vac2 and Gas1 & Gas2 times, as well as Seal only mode.

Two-Year Limited Warranty

We are confident with the quality and reliability of our products and offer a Two-Year Limited Warranty for most Accu-Seal machines. For further details please contact the Accu-Seal Sales Department. Accu-Seal machines are designed and manufactured with pride in the USA.

Compare the Features. Experience the Difference.

Equipment Specifications

CLEANROOM FEATURES

- Non-Particle Generating Venturi Vacuum System
- Isolated Exhaust Port

STANDARD FEATURES

- Retractable vacuum nozzle
- **smartVAC** Control Pad with easy to read large character LCD display
- Open ended Seal bars with 1/4" wide heating element
- Electronic Foot switch Activation
- Foot switch advance of digital timers
- E-Stop Button & Low pressure close with Jaw Obstruction Safety feature
- Pressure Regulator and Gauge
- Vacuum Gauge
- Manual Purge to clear nozzles (Gas models)
- Seal Count
- Rigid Steel Case with Powder coat Finish

SELECTABLE SEALING MODES BY MODEL

- MODEL 1 - Vacuum Sealer
 - Vacuum-Seal
 - Seal only
- MODEL 2 - Gas-Vac-Sealer
 - Vacuum-Seal
 - Gas-Vac-Seal
 - Seal only
- MODEL 3 - Gas-Vac-Sealer with Multiple Operating Modes
 - Vacuum-Seal
 - Gas-Vac-Seal
 - Vac-Gas-Seal
 - Vac1-Gas1 (1-99) + Vac2- Seal
 - Gas1-Vac1 (1-99) + Gas2-Seal
 - Seal only



- User-friendly controls that operators can learn to use in minutes.
- Open-ended Seal bars and retractable vacuum nozzle enhance production speed.

FACTORY OPTIONS

- 3/8" Seal width
- Vacuum Moisture Particle Filter
- 220V
- CE Certification

OPTIONAL ACCESSORIES

- Ergonomic Multi-Position Machine Stand
- Product Support Tray
- Exhaust Silencer
- Industrial Air Compressor

SPECIFICATIONS

- Seal Lengths: 20", 25", 30"
- Seal widths: 1/4" Standard
- Vacuum Pressure: Up to 26 in Hg Standard

REQUIREMENTS

- Power:
 - 120 Vac, 10A (20" model)
 - 220 Vac, 5A (20" model)
- Air: Requires Compressed Air Source
 - 2.5 CFM @ 90PSI

Foot Print : Length: Seal length + 3.5", Depth: 16", Height: 8"

Case Dimensions : Length: 20", Depth: 13", Height 8"

Approximate Weight: 50 Lbs



Features and specifications subject to change without notice.